



Engine	Cummins L9
Rated Power	240 kW (322 hp / 326 ps) @ 2,100 rpm
Operating Weight	30,360 kg
Standard Bucket Size	4.5 m ³
Standard Breakout Force	245 kN
Standard Dump Clearance	3,300 mm

886T WHEEL LOADER

TOUGH WORLD. TOUGH EQUIPMENT.

ENGINE

Emission Regulation	EPA Tier 3 / EU Stage III
Manufacturer	Cummins
Model	L9
Rated Power	240 kW (322 hp / 326 ps) @ 2,100 rpm
Peak Torque	1,800 N·m @ 1,200-1,400 rpm
Displacement	8.9 L
Number of Cylinders	6
Aspiration	Turbocharged & Air-to-air intercooled

TRANSMISSION

Transmission Type	Countershaft, powershift
Torque Converter	Single stage, three elements
Maximum Travel Speed, fwd	37 km/h
Maximum Travel Speed, rev	26.2 km/h
Number of Speed, fwd	4
Number of Speed, rev	3

AXLES

Differential Front Type	Limited slip
Differential Rear Type	Limited slip
Axle Oscillation	±8°

STEERING

Steering Hydraulic System	Load sensing steering
Steering Relief Pressure	

BRAKES



Service Brake Type	Wet discs brake
Service Brake Actuation	Full hydraulic
Parking Brake Type	Caliper discs brake
Parking Brake Actuation	Electro-hydraulic release

HYDRAULIC SYSTEM

Main Pump Type	Piston + Gear
Main Relief Pressure	28 MPa
Raise	5.8 s
Dump Time	1.3 s
Float Down Time	3.4 s
Hydraulic Cycle Time	10.5 s

LOADER ARM PERFORMANCE WITH STANDARD BUCKET 4.5 m³

Tipping Load - Straight (ISO 14397-1:2007)	25,300 kg
Tipping Load - Full Turn (ISO 14397-1:2007)	22,300 kg
Bucket Breakout Force	245 kN
A Maximum Hinge Pin Height	4,638 mm
B Dump Clearance at Full Height Discharge	3,390 mm
C Dump Reach at Full Height Discharge	1,237 mm
D Maximum Digging Depth, Bucket Level	100 mm
S ₁ Bucket Rollback at Ground Level	44°
S ₂ Bucket Rollback at Carry	48°
S ₃ Bucket Rollback at Maximum Height	59°
S	



Guangxi Liugong Machinery Co., Ltd.

No. 1 Liutai Road, Liuzhou, Guangxi 545007, PR China
T: +86 772 3886124 E: overseas@liugong.com
www.liugong.com

Specifications and designs are subject to change without notice. Machines shown may include optional equipment. Liugong standard and optional equipment may vary from region to region. Please consult your Liugong dealer for information specific to your area. Engine power kW is converted to horsepower (1 kW=1.3596 ps and 1 kW=1.3410 hp) in this file.

11/2025 Designed by Liugong
Replace the previous versions of 10/2025